



Specifications Ledvance LED  
Downlight Comfort Opal White  
13W/10W/7W 1430lm/1100lm/770lm  
95D - 930-940 CCT | Cutout 100mm -  
IP44 - Best Colour Rendering - Dali  
Dimmable

[View Product](#)

General Information

|                          |                                         |
|--------------------------|-----------------------------------------|
| SKU                      | 254967                                  |
| EAN                      | 4099854490866                           |
| Brand                    | Ledvance                                |
| Manufacturer Name        | DL CMFT DA D100 P 13W MS 940 OP WT LEDV |
| Any Lamp all-in warranty | 5 Years                                 |
| Average Lifetime (h)     | 100000                                  |

Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Emergency Lighting          | No Emergency Unit  |
| Tiltable                    | No                 |
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 1x18               |
| Wattage                     | 13                 |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 930 Warm White     |
| Colour temperature (Kelvin) | 3000 Warm White    |
| Colour Rendering (Ra)       | 90-99              |
| Colour of Light             | White              |

|                          |                          |
|--------------------------|--------------------------|
| Light colour options     | Single Color             |
| Beam Angle (degree)      | 95                       |
| Luminous Flux (Lumen)    | 1430                     |
| Luminous Efficacy (lm/W) | 110                      |
| Power factor             | >0.90                    |
| Unified Glare Rating     | < 23 - for general areas |
| Optical Cover            | Opal                     |
| Product Type Category    | LED Downlight            |

## Fixture Information

|                        |                        |
|------------------------|------------------------|
| Mounting Method        | Recessed               |
| Cut out (mm)           | 100                    |
| IP-rating              | IP44                   |
| Impact Protection (IK) | IK03 - 0.35 joule      |
| Operating Temperature  | -20 to +40             |
| Housing                | Aluminium              |
| Colour of the Fixture  | White                  |
| Fixture Connection     | PI [Push-in connector] |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 48  |
| Diameter (mm) | 116 |

## Why Any-lamp?

## Sensor Information

Type of sensor



Order from the **largest lighting specialist** in Europe

No Sensor



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

