



Specifications Noxion LED Panel Delta Pro V3.0 30W 3960lm - 830 Warm White | 60x60cm - UGR <19 - Philips Xitanium Driver - Emergency 1H

[View Product](#)

## General Information

|                          |                                                                                                    |
|--------------------------|----------------------------------------------------------------------------------------------------|
| SKU                      | 243397                                                                                             |
| EAN                      | 8719157035262                                                                                      |
| Brand                    | Noxion                                                                                             |
| Manufacturer Name        | Noxion LED Panel Delta Pro V3 30W 3960lm 3000K 600*600 UGR<19 (4x18W eqv.) + Emergency integration |
| Any Lamp all-in warranty | 6 Years                                                                                            |
| Average Lifetime (h)     | 50000                                                                                              |
| Series                   | Delta Pro                                                                                          |

## Technical Information

|                             |                 |
|-----------------------------|-----------------|
| Technology                  | LED Integrated  |
| Replaces (Watt)             | 4x18            |
| Wattage                     | 30              |
| Voltage (V)                 | 220-240         |
| Dimmable                    | Not Dimmable    |
| Colour Code                 | 830 Warm White  |
| Colour temperature (Kelvin) | 3000 Warm White |
| Colour Rendering (Ra)       | 80-89           |
| Colour of Light             | White           |
| Light colour options        | Single Color    |
| Luminous Flux (Lumen)       | 3960            |

|                          |                   |
|--------------------------|-------------------|
| Luminous Efficacy (lm/W) | 132               |
| IP-rating                | IP20              |
| Impact Protection (IK)   | IK03 - 0.35 joule |
| Fixture Connection       | Push Terminal     |
| Finish of Reflector      | Frosted           |
| Power factor             | >0.90             |
| Product Type Category    | LED Panel         |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PS (Polystyrene)               |
| Operating Temperature | +10 to +45                     |
| Emergency Lighting    | 1H Emergency Light             |
| Colour of the Fixture | White                          |
| Housing               | Aluminium                      |
| Colour of material    | White                          |

## Dimensions

|                |         |
|----------------|---------|
| LED panel size | 60x60cm |
| Length (mm)    | 595     |
| Width (mm)     | 595     |
| Height (mm)    | 10      |

## Sensor Information

Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor



Up to **7 years warranty**

No Sensor



**Easy** return process